





BB60 & BB72 BANQUET CARTERS


heated preplated carters for
8 3/4" to 10 1/2" plate diameter




BB60
Front View



BB60
Top View



BB72
Top View



BB72
Front View

Carter-Hoffmann C.A.D.
Drawing Scale: 1/4" = 1'

CARTER-HOFFMANN
11 FOOD SERVICE EQUIPMENT
HEATED SERVERS

SPECIFICATIONS

Model Number	Plate Capacity			Number of Shelves	Shelf Size	Clearance Between Shelves	Casters	Dimensions			Shipping Weight (Lbs.)
	Capacity with "P" Carriers (Quantity)	Capacity with "C" Carriers (Quantity)	Capacity Without Carriers					High	Deep	Wide	
<input type="checkbox"/> BB60	60 Plates in 6 (10P) Carriers	Up to 72 Plates in 6 (10C) Carriers	Up to 72 Plates Stacked on Shelves	2	22" x 32" (559 x 838 mm)	16 (406 mm)	6" Dia. (152 mm) 2 Swivel 2 Rigid	46" (1168 mm)	30 1/2" (777 mm)	40 1/2" (1029 mm)	290 (132 kgs)
<input type="checkbox"/> BB72	72 Plates in 9 (8P) Carriers	Up to 90 Plates in 9 (8C) Carriers	Up to 90 Plates Stacked on Shelves	3	22" x 32" (559 x 838 mm)	13 (330 mm)	6" Dia. (152 mm) 2 Swivel 2 Rigid	54" (1372 mm)	30 1/2" (777 mm)	40 1/2" (1029 mm)	310 (141 kgs)

NOTE: Capacities shown for use with Plate Covers depend on stacked height of plate and cover.

CONSTRUCTION . . . Completely welded cabinet construction and top corners, with outer cabinet formed to base and welded. All seams turned in to eliminate raw edges.

CABINET MATERIALS . . . Nickel-bearing type 300 series stainless steel, 20 gauge polished exterior wall, 24 gauge interior.

BASE FRAME . . . 12 gauge stainless steel full depth bolsters with 1" x 1" stainless steel perimeter channel supports.

CASTERS . . . 6" diameter, industrial grade caster with polyurethane tread, delrin sleeve axle bearing and double ball bearing swivel. Zerk grease fittings. Plate mounted and bolted to base in offset wheel ahead pattern. Two casters fitted with brakes.

BUMPER . . . Non-marking gray vinyl bumper set in heavy duty 3/16" extruded aluminum frame with reinforced corner "cut-outs".

INSULATION . . . High density fiberglass insulation, 1" thick continuous wrap-around type with 1 1/2" thickness on top.

DOORS . . . Double panel stainless steel doors completely welded with cavity filled with high density fiberglass insulation. Decorative vinyl feature stripe.

GASKETS . . . High temperature gasket.

LATCHES . . . Flush mounted, heavy duty sliding latch with exclusive grip handle.

HINGES . . . Concealed, stainless steel hinge with 5/16" pin.

HANDLES (two) . . . Horizontal full width heavy duty aluminum push handles with back-up plates.

SHELVES . . . Welded chrome plated removable wire shelves.

CARRIERS . . . "P" or "C" carriers are available. Specify type, if any, when ordering. "P" type holds 8 3/4" to 10 1/2" open plates, while "C" type holds up to 10 1/2" covered plates.

THERMOMETER . . . Dial type with sensing bulb and sensing bulb protector.

HEATING SYSTEM...Bottom mounted heater. Stainless steel construction. Removable without tools. 1600 watt inconel-sheathed heating element. High impedance protected, internally cooled fan motor. Full range thermostat and power indicating light.

ELECTRICAL CHARACTERISTICS... Operates on 120 volts, 60 cycle, single phase, 1650 watts, 13.7 amps. Ten foot rubber cord with 3 prong grounding plug. NEMA 5-15P.

PERFORMANCE . . . Capable of heating to 200° F. Preheat to 160° F. Approximately 20 minutes.

ACCESSORIES/OPTIONS . . .

- Top Transport Latch
- Locking Paddle Latch
- Menu Card Holder
- Lexan Thermometer Cover
- Retractable Cord Reel
- Canned heat adapters
- Full Pneumatic Caster
- Semi-Pneumatic Caster
- 220 volt/60 cycle/1 phase
- 240 volt/50 cycle/1 phase



Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN CORP.

1551 McCormick Ave., Mundelein, IL 60060
Tel (847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com

Printed in U.S.A. B30 0599
The name Carter-Hoffmann is a registered trade name of Carter-Hoffmann Corp.