




BB64 & PS96 BANQUET CARTERS

heated preplated carters for
8 3/4" to 10 1/2" plate diameter




BB64




BB64
Front View


Carter-Hoffmann C.A.D.
Drawing Scale: 1/4" = 1"



BB64
Top View



PS96
Top View



PS96
Front View

Model Number	Plate Capacity			Number of Shelves	Shelf Size	Clearance Between Shelves	Casters	Dimensions			Shipping Weight (Lbs.)
	Capacity with "P" Carriers (Quantity)	Capacity with "C" Carriers (Quantity)	Capacity Without Carriers					High	Deep	Wide	
<input type="checkbox"/> BB64	64 Plates in Eight (8P) Carriers	Up to 80 Plates in Eight (8C) Carriers	Up to 80 Plates Stacked on Shelves	4	22 3/4" x 26 1/2" (578 mm) (673 mm)	13" (330mm)	6" Dia. (152mm) 4 Swivel	70 3/4" (1797 mm)	36" (914 mm)	30 3/4" (781 mm)	336 (153 kgs)
<input type="checkbox"/> PS96	96 Plates in Twelve (8P) Carriers	Up to 120 Plates in Twelve (8C) Carriers	Up to 120 Plates Stacked on Shelves	3	22" x 42" (559 mm) (1067 mm)		6" Dia. (127 mm) 2 Swivel 2 Rigid	54" (1372 mm)	27 1/2" (698 mm)	48 1/4" (1238 mm)	348 (158 kgs)

NOTE: Capacities shown for use with Plate Covers depend on stacked height of plate and cover.

CONSTRUCTION . . . Completely welded cabinet construction and top corners, with outer cabinet formed to base and welded. All seams turned in to eliminate raw edges.

CABINET MATERIALS . . . Nickel-bearing type 300 series stainless steel, 20 gauge polished exterior wall, 24 gauge interior.

BASE FRAME . . . 12 gauge stainless steel full depth bolsters with 1" x 1" stainless steel perimeter channel supports.

CASTERS . . . 6" diameter, industrial grade, polysealed roller bearing casters. Plate mounted and bolted to base in offset wheel ahead pattern. Two casters fitted with brakes.

BUMPER . . . Non-marking gray vinyl bumper set in heavy duty 3/16" extruded aluminium frame with reinforced corner "cut-outs".

BUMPER (PS96 only) . . . Four non-marking corner bumpers.

INSULATION . . . High density fiberglass insulation, 1" thick continuous wrap-around type with 1 1/2" thickness on top.

DOORS . . . Double panel stainless steel doors completely welded with cavity filled with high density fiberglass insulation. Decorative vinyl feature stripe on BB64 only.

GASKETS . . . High temperature gasket.

LATCHES . . . Flush mounted, heavy duty sliding latch with exclusive grip handle.

HINGES . . . Concealed, stainless steel hinge with 5/16" pin.

HANDLES (two) . . . Horizontal full width heavy duty aluminum push handles with back-up plates.

SHELVES . . . Welded chrome plated removable wire shelves.

CARRIERS . . . "P" or "C" carriers are available. Specify type, if any, when ordering. "P" type holds 8 3/4" to 10 1/2" open plates, while "C" type holds up to 10 1/2" covered plates.

THERMOMETER . . . Dial type with sensing bulb and sensing bulb protector.

HEATING SYSTEM . . . Bottom mounted heater. Stainless steel construction. Removable without tools. 1600 watt inconel-sheathed heating element. High impedance protected, internally cooled fan motor. Full range thermostat and power indicating light

ELECTRICAL CHARACTERISTICS . . . Operates on 120 volts, 60 cycle, single phase, 1650 watts, 13.7 amps. Ten foot rubber cord with 3 prong grounding plug. NEMA 5-15P.

PERFORMANCE . . . Capable of heating to 200° F. Preheat to 160° F. Approximately 20 minutes.

ACCESSORIES/OPTIONS . . .

- Top Transport Latch
- Locking Paddle Latch
- Menu Card Holder
- Lexan Thermometer Cover
- Cold Plate
- Retractable Cord Reel
- Canned heat adapters
- Full Pneumatic Caster
- Semi-Pneumatic Caster
- Alternate Electrical Configurations



Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN CORP.

1551 McCormick Ave., Mundelein, IL 60060
Tel (847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com