



UTILITY TRAY TRANSPORT For Healthcare Facilities



**UC2S2433
Utility Cart**



**TT104
Stacking Tray
Transport Cart**

STACKING TRAY TRANSPORT

Model Number	Insulated Tray Capacity	Overall Dimensions						Caster Diameter		Shipping Weight	
		Height		Depth		Width		in	mm	lbs	kg
		in	mm	in	mm	in	mm				
<input type="checkbox"/> TT48	48*	40 ³ / ₈	1026	30 ¹ / ₄	768	36 ³ / ₄	933	5	127	150	68
<input type="checkbox"/> TT84	72 - 84*	40 ³ / ₈	1026	30 ¹ / ₄	768	55 ³ / ₄	1416	5	127	170	77
<input type="checkbox"/> TT104	104 assorted correctional	46 ¹ / ₂	1181	28	711	49	1245	5	127	367	166
<input type="checkbox"/> TT136	136 assorted correctional	46 ¹ / ₂	1181	28	711	64 ¹ / ₂	1638	5	127	457	207

*Tray Dimensions: 19.25" x 13" x 2.38"

CONSTRUCTION... Completely welded straight line modular construction. All horizontal supports are welded and polished to vertical uprights to form one-piece rigid cart. Extra welds on bottom supports for maximum support and added durability. Vertical uprights are gusseted for additional support. Includes 96" tray strap with buckle to secure insulated stacking trays in place.

SHELVES... Stainless steel top shelf with marine edge. Lower shelf is flat.

MATERIAL... All stainless steel construction; Framework and supports constructed of 1" x 18 gauge seamless, polished stainless steel tubing.

PUSH HANDLE... Full width 1" stainless steel tubular push handle mounted to swivel end.

CASTERS... Stem mounted 5" diameter red Performa casters. All full ball bearing swivel. Two fitted with brakes.

OPTIONS AND ACCESSORIES...
 additional 96" tray strap with buckle

UTILITY CARTS

Model Number	Type	Overall Dimensions						Caster Diameter		Shipping Weight	
		Height		Depth		Width		in	mm	lbs	kg
		in	mm	in	mm	in	mm				
<input type="checkbox"/> UC2S2433	2-shelf; 24 ³ / ₄ " shelf spacing	36	914	26	660	36 ³ / ₄	933	5	127	94	43
<input type="checkbox"/> UC3S2433	3-shelf; 11 ³ / ₄ " shelf spacing	36	914	26	660	36 ³ / ₄	933	5	127	109	49

CONSTRUCTION... All welded stainless steel construction. Stainless steel tubular vertical and horizontal supports.

SHELVES... Top shelf flanged up on three sides. Lower shelves are flat. UC2S2433 has two shelves and UC3S2433 has 3 shelves. 700 lb capacity.

MATERIAL... All stainless steel construction; Framework and supports constructed of 1" x 18 gauge seamless, polished stainless steel tubing.

PUSH HANDLE... Full width 1" stainless steel tubular push handle mounted to swivel end. Donut bumpers on each end.

BUMPERS... Soft durometer cushioned corner bumpers, bolted to four corners.

CASTERS/LEGS... Stem mounted 5" diameter red Performa casters. All full ball bearing swivel. Two fitted with brakes.

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN

1551 McCormick Ave., Mundelein, IL 60060
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com

SPECIFICATIONS